

Product data sheet

Specifications

SQUARE D



Overload Relay, Type S, melting alloy, separate mount overload, NEMA size 4, 3 pole, 3 phase, 133A, 600VAC

9065SEO15

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range of Product	Separate Mounting
Thermal overload type	Melting alloy

Complementary

NEMA size	4
Number of thermal units required	3
Mounting Support	Panel
[Ue] rated operational voltage	600 V AC
Height	7.0 in (177 mm)
Width	5.3 in (134.9 mm)
Depth	5.8 in (146.1 mm)

Ordering and shipping details

Category	US10CP121661
Discount Schedule	OCP1
GTIN	785901850823
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	6.40 in (16.256 cm)
Package 1 Width	8.50 in (21.59 cm)
Package 1 Length	6.40 in (16.256 cm)
Package weight(Lbs)	4.290 lb(US) (1.946 kg)

Contractual warranty

Warranty	18 months
----------	-----------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Not compliant
California proposition 65	<p>WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov</p>

Use Again

Repack and remanufacture

Take-back	No
-----------	----