

Product data sheet

Characteristics

9070SK2000A3D1

Transformer disconnect, 2000VA, 240x480VAC primary, 120VAC secondary, without outlet, flange switch, Type 12

Main

Product	Transformer Disconnect
Certifications	CSA[RETURN]UL Listed
Enclosure Type	NEMA 12 standard
Insulation Temperature	356 °F (180 °C)
Phase	1 phase
Primary Voltage	240 x 480 V
Power Rating	2000 VA
Secondary Voltage	120 V
Temperature Rise	115 °C
Electrical Connection	Screw clamp terminals
Type	SK

Ordering and shipping details

Category	US10CP821694
Discount Schedule	0CP8
GTIN	785901834526
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.0000000000 in (38.1 cm)
Package 1 Width	18.0000000000 in (45.72 cm)
Package 1 Length	24.0000000000 in (60.96 cm)
Package 1 Weight	77.0009 lb(US) (34.927 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes

Contractual warranty

Warranty	18 months
----------	-----------