

# Product data sheet

Specifications

SQUARE D



Transformer, Type T, industrial control, 1500VA, 1 phase, 380/400/415V primary, 115/230V secondary, 115C rise

9070T1500D33

**Product availability:** Non-Stock - Not normally stocked in distribution facility

## Main

|              |                                |
|--------------|--------------------------------|
| Product Type | Industrial Control Transformer |
| Type         | T                              |

## Complementary

|                                |  |
|--------------------------------|--|
| Number of Phases               | 1 phase  |
| Power Rating                   | 1500 VA UL<br>1500 VA CSA<br>1500 VA NOM<br>1000 VA CE |
| Primary to Secondary Voltage   | 380/400/415 V 115/230 V                                |
| Temperature Rise               | 115 °C   |
| Electrical Connection          | Screw clamp terminals                                  |
| Height                         | 6.17 in (156.72 mm)                                    |
| Width                          | 7.06 in (179.32 mm)                                    |
| Depth                          | 5.92 in (150.37 mm)                                    |
| Fingersafe Cover Compatibility | FSC2   |

## Environment

|                        |                         |
|------------------------|-------------------------|
| Certifications         | CSA<br>cUL<br>UL Listed |
| Enclosure Type         | Not rated (open device) |
| Insulation Temperature | 356 °F (180 °C)         |

## Ordering and shipping details

|                   |              |
|-------------------|--------------|
| Category          | US10CP816206 |
| Discount Schedule | OCP8         |
| GTIN              | 785901322351 |
| Returnability     | No           |
| Country of origin | US           |

## Packing Units

|                        |     |
|------------------------|-----|
| Unit Type of Package 1 | PCE |
| Nbr. of units in pkg.  | 1   |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

|                     |                           |
|---------------------|---------------------------|
| Package 1 Height    | 11.00 in (27.94 cm)       |
| Package 1 Width     | 11.25 in (28.575 cm)      |
| Package 1 Length    | 14.19 in (36.043 cm)      |
| Package weight(Lbs) | 34.300 lb(US) (15.558 kg) |

---

## Contractual warranty

---

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

## Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

|  |   |
|--|---|
| Packaging made with recycled cardboard | Yes   |
| Packaging without single use plastic   | No  |
| <a href="#">EU RoHS Directive</a>      | Compliant with Exemptions   |
| REACH Regulation                       | <a href="#">REACH Declaration</a>   |
| California proposition 65              | WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="#">www.P65Warnings.ca.gov</a> |
| PVC free                               | Yes   |

## Use Again

### Repack and remanufacture

|                     |  |
|---------------------|--|
| Circularity Profile | No need of specific recycling operations |
| Take-back           | No                                       |