



Complementary

Power Rating	750 VA UL[RETURN]750 VA CSA[RETURN]750 VA NOM[RETURN]500 VA CE
Primary to Secondary Voltage	600 V 120 V 575 V 115 V 550 V 110 V
Fuse type	0.41 x 1.50 in CC top
Temperature rise	115 °C
Height	5.73 in (145.54 mm)
Width	5.25 in (133.35 mm)
Depth	5.66 in (143.76 mm)
Material	Copper: winding

Environment

Product Certifications	CSA file LR37055 guide 184-N-90[RETURN]CE[RETURN]UL listed file E61239
Insulation temperature	356 °F (180 °C)

Ordering and shipping details

Category	US10CP816207
Discount Schedule	0CP8
GTIN	785901763512
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.00 in (17.78 cm)
Package 1 Width	9.00 in (22.86 cm)
Package 1 Length	9.00 in (22.86 cm)
Package 1 Weight	17.20 lb(US) (7.802 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
RECh Regulation	RECh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Circularity Profile	No need of specific recycling operations
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------
