

Product data sheet

Specifications

SQUARE D



Power distribution block, Linergy, 1 pole, 2 line, 6 load, 350A Cu, 600V

9080LBC263206

Product availability: Stock - Normally stocked in distribution facility

Main

Range	9080LB
Product	Power Distribution Block
Current Rating	350 A copper
Short Circuit Current Rating	65 kA

Complementary

Voltage Rating	600 V AC/DC
Mounting Type	Surface mount
Number of poles	2
Terminals per Pole	2 load 6 line
Wire Size	Line 2, AWG 14...AWG 2/0, copper Load 6, AWG 14...AWG 4, copper
Electrical Connection	Tin plated copper lugs
SCCR	100 kA UL 508 A
Ambient Air Temperature for Operation	-40...150 °C (-40...302 °F)
Block Material	Phenolic: block
Terminal Tightening Torque	Line lug 40 lbf.in (4.5 N.m) AWG 8 copper Line lug 35 lbf.in (4.0 N.m) AWG 14...AWG 10 copper Line lug 120 lbf.in (13.6 N.m) AWG 6...AWG 2/0 copper Load lug 35 lbf.in (4.0 N.m) AWG 14...AWG 4 copper
Wire stripping length	Load: 0.38 in (9.65 mm) for top connection Load: 0.75 in (19.05 mm) for bottom connection Line: 0.75 in (19.05 mm)
Height	4 in (101.6 mm)
Width	3.47 in (88.14 mm)
Depth	2.61 in (66.29 mm)
End Barrier	9080LB32

Environment

Certifications	UL recognized E60616 CCN XCFR2 CE CSA file 70361 class 6228 01
----------------	--

Ordering and shipping details

Category	US10CP121711
----------	--------------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Discount Schedule	0CP1
GTIN	785901157120
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	3.00 in (7.620 cm)
Package 1 Width	4.40 in (11.176 cm)
Package 1 Length	5.30 in (13.462 cm)
Package weight(Lbs)	20.800 oz (589.670 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	16
Package 2 Height	11.00 in (27.940 cm)
Package 2 Width	9.70 in (24.638 cm)
Package 2 Length	13.60 in (34.544 cm)
Package 2 Weight	22.320 lb(US) (10.124 kg)

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	REACH Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

 Repack and remanufacture	
Take-back	No

Technical Illustration

Dimensions

