SQUARE D

Operating mechanism, flange mounted, variable depth, handle mechanism, 4in handle, NEMA 4X enclosure

9422A4

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Product	Handle Mechanism
For Use With	Disconnect switches (30...200 A)

Complementary

Product Type	Variable depth
Product destination	disconnect switches (30...200 A)
Enclosure Types	NEMA 4/4X enclosures
Handle Length	4 in (101.6 mm)

Ordering and shipping details

Category	US10CP121732
Discount Schedule	0CP1
GTIN	785901964155
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.900 in (4.826 cm)
Package 1 Width	3.800 in (9.652 cm)
Package 1 Length	9.300 in (23.622 cm)
Package weight(Lbs)	2.670 lb(US) (1.211 kg)

Contractual warranty

Warranty	18 months

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant**
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**
PVC free	**Yes**

Use Again

Repack and remanufacture

Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**

Dimensions Drawings

Approximate Dimensions

in.
[mm]

3.53
[90] Max.
on A1 & A2

2.16
[55]

.88
[22]

Enclosure
Flange

2.00
[51]

C/L of
Operating
Mechanism

Door interlock
defeater screw

6.13 (A1 & A2)
4.50 (A3 & A4)
10.13 (A9 & A10)

Stiffener
Bracket

1.06
[27]

.53
[14]

.50
[13]

ON

OFF
RESET

4.69
[119]

5.69
[145]

1.13
[29]