

Product data sheet

Specifications

SQUARE D



Disconnect mechanism, circuit breaker, variable depth, 600A, 3 pole, operator only, for PowerPacT D and L breakers

9422RS1

Product availability: Stock - Normally stocked in distribution facility

Main

Range	9422R
Product	Circuit Breaker Mechanism
Mounting Type	Flange rod variable depth
Certifications	CSA UL Recognized
Circuit Breaker Type	MG-NSJ 3 PowerPac D 3
Handle Type	Ordered separately

Ordering and shipping details

Category	US10CP121732
Discount Schedule	0CP1
GTIN	785901551430
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	6.80 in (17.272 cm)
Package 1 Width	12.30 in (31.242 cm)
Package 1 Length	13.30 in (33.782 cm)
Package weight(Lbs)	7.339 lb(US) (3.329 kg)

Contractual warranty

Warranty	18 months
----------	-----------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Again

 Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No