



## Main

Range	9422T
Product	Disconnect Switch
Disconnect Type	Non-fusible disconnect switch

## Complementary

Mounting Type	Flange cable variable depth
Current Rating	60 A
Horsepower Rating	15 Hp 200 V AC 15 Hp 230 V AC 30 Hp 460 V AC 50 Hp 575 V AC 10 hp 250 V DC
Handle Type	Ordered separately

## Environment

Certifications	CSA[RETURN]UL Recognized
----------------	--------------------------

## Ordering and shipping details

Category	US10CP121732
Discount Schedule	OCP1
GTIN	785901811589
Returnability	No
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.50 in (19.05 cm)
Package 1 Width	11.0000000000 in (27.94 cm)
Package 1 Length	16.50 in (41.91 cm)
Package 1 Weight	9.780 lb(US) (4.436 kg)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>

## Contractual warranty

Warranty	18 months
----------	-----------