

Product data sheet

Specifications

SQUARE D



Disconnect mechanism, flange mounted, disconnect switch auxiliary contact kit, 15A, 1 pole, SPDT

9999TC10

Product availability: Stock - Normally stocked in distribution facility

Main

Range	Square D
Product or Component Type	Interlock
Device Application	Control

Complementary

Range compatibility	Square D Disconnect Switch
[Ie] rated operational current	15 A120 V AC 50/60 Hz 15 A240 V AC 50/60 Hz 15 A480 V AC 50/60 Hz 15 A600 V AC 50/60 Hz
Height	4.16 in (105.66 mm)
Depth	1.44 in (36.58 mm)
Net Weight	0.51 lb(US) (0.23 kg)

Ordering and shipping details

Category	US10CP121761
Discount Schedule	0CP1
GTIN	785901858478
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	3.200 in (8.128 cm)
Package 1 Width	4.200 in (10.668 cm)
Package 1 Length	6.700 in (17.018 cm)
Package weight(Lbs)	8.480 oz (240.404 g)

Contractual warranty

Warranty	18 months
----------	-----------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Under investigation

Use Again

 Repack and remanufacture	
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.