



End Closure, I-Line Busway, max 800A rated, end caps, aluminium/copper [TAA]

ACF43EC

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Product	End Closure
Range	I-Line

Complementary

Rated Operational Voltage	600 V AC/DC 50/60 Hz	
Length	4.84 in (122.94 mm)	
Height	7.06 in (179.32 mm)	
Width	1 in (25.4 mm)	
For Use with	Busbar trunking 800 A aluminium end caps Busbar trunking 1000 A copper end caps	

Environment

Standards UL 857

CSA C22.2 No 27:1994 IEC 61439-6

Ordering and shipping details

Category	US10PE820199
Discount Schedule	0PE8
GTIN	785901816102
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE	
Nbr. of units in pkg.	1	
Package 1 Height	5.50 in (13.97 cm)	
Package 1 Width	8.80 in (22.352 cm)	
Package 1 Length	9.00 in (22.86 cm)	
Package weight(Lbs)	4.310 lb(US) (1.955 kg)	

Compliance

Compliance	TAA
	BAA via COTS

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Contractual warranty

Warranty

18 months

Jul 22, 2025



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No