

Product data sheet

Specifications

SQUARE D



End Closure, I-Line Busway, max 1600A rated, end caps, aluminium [TAA]

ACF88EC

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Product	End Closure
Range	I-Line

Complementary

Rated Operational Voltage	600 V AC/DC 50/60 Hz
Length	9.34 in (237.24 mm)
Height	7.06 in (179.32 mm)
Width	1 in (25.4 mm)
For Use with	Busbar trunking 1600 A aluminium end caps

Environment

Standards	UL 857 CSA C22.2 No 27:1994 IEC 61439-6
-----------	---

Ordering and shipping details

Category	US10PE820199
Discount Schedule	OPE8
GTIN	785901816171
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	9.33 in (23.7 cm)
Package 1 Width	0.98 in (2.5 cm)
Package 1 Length	7.05 in (17.9 cm)
Package weight(Lbs)	6.720 lb(US) (3.048 kg)

Compliance

Compliance	TAA BAA via COTS
------------	---------------------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Contractual warranty

Warranty

18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Again

Repack and remanufacture

Circularity Profile	No need of specific recycling operations
Take-back	No