

Product data sheet

Specifications

SQUARE D



Transformer, dry type, DOE 2016,
500kVA, 3 phase, 480V delta
primary, 208Y/120V secondary,
30J, 150C rise, Cu

EX500T68HCU

Product availability: Non-Stock - Not normally stocked in
distribution facility

Main

Range of Product	Square D
Product or Component Type	Transformer
Device short name	DOE 2016
Transformer type	Energy efficient
Device Application	Low voltage electrical distribution

Complementary

Box number	30J
Phase	3 phase
Rated operational power in VA	500 kVA
Network Frequency	60 Hz
type of cooling	Natural convection
Primary Voltage	480 V delta
Number of tap-offs	2 2.5 % FCAN 2 2.5 % FCBN
Secondary voltage	208Y/120 V
Coil Material	Copper
Basic IMP level (BIL)	10 kV
Temperature Rise	150 °C 220 °C insulated
DOE Efficiency	99.32 % at 35 % load factor , 167 °F (75.0 °C)
Sound Level	6 dB NEMA ST-20 56 dB
%IZ	0.048 %
%IX	0.0465 %
X/R Ratio	4.37
Let Through Current	29.1 kA
Transformer Losses	667.0 no load (core loss) 5324.0 load loss (coil loss)
Transformer BTU/HR	2776.4877338844476 16.6 % 3411.2889644999996 25 % 6817.459715999999 50 % 12494.410968499998 75 % 20442.142722 100 %

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Height	71.0 in (1803 mm)
Depth	37.9 in (963 mm)
Width	48.3 in (1226 mm)
Net Weight	3705.004 lb(US) (1680.56 kg)
Mounting support	Floor Floor, with 7400FMB
Degree of protection	UL type 1 UL type 2, with 7400DS30J UL type 3R, with 7400WS30J
Electrical connection	4 Hole Nema Pad primary 0.4 in (11.1 mm) 6 Hole Nema Pad secondary 0.4 in (11.1 mm) 8 Hole Nema Pad sec - XO 0.4 in (11.1 mm)

Environment

Ambient Air Temperature for Operation	104 °F (40 °C)
Average ambient air temperature for operation	30 °C
Standards	UL 1561 CSA C22.2 No 47 NEMA ST-20

Ordering and shipping details

Category	US1PE2X16252
Discount Schedule	PE2X
GTIN	785901694366
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	82.01 in (208.3 cm)
Package 1 Width	47.99 in (121.9 cm)
Package 1 Length	55.98 in (142.2 cm)
Package weight(Lbs)	3960.01 lb(US) (1796.23 kg)



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

 Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	91945
Environmental Disclosure	Product Environmental Profile

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	REACH Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl Glycidyl Ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Again

 Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No