

# Product data sheet

Specifications



## TeSys GB2 thermal magnetic circuit protector, 1 P, 5 A, Id = 66 A

GB2CB10

**Product availability: Stock - Normally stocked in distribution facility**

### Main

Range	TeSys
Product name	TeSys GB2
Device short name	GB2
Product or Component Type	Circuit breaker
Device Application	Control
Poles description	1P
Network type	AC/DC
Utilisation category	Category A IEC 60947-2 DC-12 IEC 60947-5-1 DC-13 IEC 60947-5-1
Network frequency	50/60 Hz IEC 60947-2
Breaking capacity	2 kA Icu 230/240 V AC 50/60 Hz IEC 60947-2
[Ics] rated service short-circuit breaking capacity	75 % 230/240 V AC 50/60 Hz IEC 60947-2
Trip unit technology	Thermal-magnetic
Magnetic tripping current	66 A

### Complementary

Mounting Mode	By clips
Mounting Support	Rail Plate
Mounting position	Horizontal Vertical
Control Type	Toggle
Line Rated Current	5 A
[Ue] rated operational voltage	250 V AC 50/60 Hz IEC 60947-2 277 V AC 60 Hz CSA C22.2 No 235 277 V AC 60 Hz UL 1077 48 V DC
[Uimp] rated impulse withstand voltage	4 kV IEC 60947-2
Power dissipation per pole	2 W
Mechanical durability	8000 cycles
Electrical durability	8000 cycles
Connections - terminals	connector 1 0.001...0.009 in <sup>2</sup> (0.75...6 mm <sup>2</sup> )solid without cable end connector 2 0.001...0.006 in <sup>2</sup> (0.75...4 mm <sup>2</sup> )solid without cable end connector 1 0.001...0.006 in <sup>2</sup> (0.75...4 mm <sup>2</sup> )flexible with cable end connector 2 0.001...0.004 in <sup>2</sup> (0.75...2.5 mm <sup>2</sup> )flexible with cable end

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Tightening torque</b>	10.6 lbf.in (1.2 N.m) connector
<b>Mechanical robustness</b>	Shocks 22 Gn for 20 ms IEC 60068-2-27 Vibrations 5 Gn, 5...110 Hz IEC 60068-2-6
<b>Quantity per Set</b>	Set of 6
<b>9 mm pitches</b>	2
<b>Height</b>	2.9 in (74 mm)
<b>Width</b>	0.6 in (15 mm)
<b>Depth</b>	2.6 in (67 mm)

## Environment

<b>Standards</b>	EN/IEC 60947-1 EN/IEC 60947-2 CSA C22.2 No 235 UL 1077
<b>Product Certifications</b>	UL CSA
<b>Protective treatment</b>	TC
<b>IP degree of protection</b>	IP20 IEC 60529
<b>Ambient air temperature for operation</b>	-4...140 °F (-20...60 °C)
<b>Ambient Air Temperature for Storage</b>	-40...176 °F (-40...80 °C)
<b>Fire resistance</b>	1760 °F (960 °C) IEC 60695-2-1
<b>Operating altitude</b>	9842.52 ft (3000 m)

## Ordering and shipping details

<b>Category</b>	US1000I22631
<b>Discount Schedule</b>	000I
<b>GTIN</b>	3389110214635
<b>Returnability</b>	Yes
<b>Country of origin</b>	FR

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Nbr. of units in pkg.</b>	1
<b>Package 1 Height</b>	3.740 in (9.500 cm)
<b>Package 1 Width</b>	4.134 in (10.500 cm)
<b>Package 1 Length</b>	3.740 in (9.500 cm)
<b>Package weight(Lbs)</b>	1.869 oz (53.000 g)
<b>Unit Type of Package 2</b>	BB1
<b>Number of Units in Package 2</b>	6
<b>Package 2 Height</b>	3.346 in (8.500 cm)
<b>Package 2 Width</b>	3.740 in (9.500 cm)
<b>Package 2 Length</b>	3.150 in (8.000 cm)
<b>Package 2 Weight</b>	11.852 oz (336.000 g)
<b>Unit Type of Package 3</b>	S02

---

<b>Number of Units in Package 3</b>	72
<b>Package 3 Height</b>	5.906 in (15.000 cm)
<b>Package 3 Width</b>	11.811 in (30.000 cm)
<b>Package 3 Length</b>	15.748 in (40.000 cm)
<b>Package 3 Weight</b>	9.517 lb(US) (4.317 kg)

---

## **Contractual warranty**

---

<b>Warranty</b>	18 months
-----------------	-----------



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 3

Environmental Disclosure [Product Environmental Profile](#)

### Use Better

#### Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic Yes

[EU RoHS Directive](#) Compliant

REACH Regulation [REACH Declaration](#)

California proposition 65 WARNING: Cancer - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)


Halogen content performance Halogen free plastic parts product

### Use Again

#### Repack and remanufacture

Circularity Profile No need of specific recycling operations

Take-back No

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.