

H361DSEI

Safety switch, heavy duty, fusible, 30A, 3 poles, 20 hp, 20 hp, 600 VAC/DC, NEMA 4, 4X, 5, 304 steel, interlock kit



Main

Product	Single Throw Safety Switch
Current Rating	30 A
Number of Poles	3
Voltage Rating	600 V AC/DC
Wire Size	AWG 12...AWG 6 aluminium AWG 14...AWG 6 copper
Disconnect Type	Fusible disconnect
Mounting Type	Surface
Factory Installed Neutral	None
Duty Rating	Heavy duty
Certifications	UL listed file E2875
Enclosure Rating	NEMA 4/4X/5 stainless steel 304

Complementary

Maximum Horse Power Rating	5 Hp 480 V AC 50...60 Hz 3 phase NEC 240.6 15 Hp 480 V AC 50...60 Hz 3 phase NEC 430.52 7.5 Hp 600 V AC 50...60 Hz 3 phase NEC 240.6 20 Hp 600 V AC 50...60 Hz 3 phase NEC 430.52 5 Hp 250 V DC 15 hp 600 V DC
Width	8.67 in (220.22 mm)
Height	14.93 in (379.22 mm)
Maximum Depth	5.11 in (129.79 mm)
Tightening torque	45 Lbf.in (5.08 N.m) 0.02 in ² (13.3 mm ²) AWG 6) 40 Lbf.in (4.52 N.m) 0.01 in ² (8.367 mm ²) AWG 8) 35 lbf.in (3.95 N.m) 0.00...0.01 in ² (2.06...5.261 mm ²) AWG 14...AWG 10)

Ordering and shipping details

Category	00160-DE1 MISC
Discount Schedule	DE1
GTIN	00785901132509
Package weight(Lbs)	13.55 lb(US) (6.146 kg)
Returnability	No
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes

China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------
