Product data sheet

Specifications



Interior, I-Line Panelboard, HCJ, 600A, main lugs, 63in CB space, for 32in W x 73in H x 9.5in D box, Cu bus

HCJ32736CU

Product availability: Stock - Normally stocked in distribution facility

Main

Range	I-Line
Product or Component Type	Interiors
Circuit Breaker Type	B-Frame J-frame H-frame Q-Frame QO
Enclosure Type	Distribution enclosure

Complementary

Main Type	Main lugs
Width	26.44 in (671.58 mm)
Height	48.02 in (1219.71 mm)
Depth	8.7 in (221.0 mm)
Localization on Device	Interior
Product Destination	Enclosure HCJ 32 in (812.8 mm) 73 in (1854.2 mm) 9.5 in (241.3 mm)
Rated Current	600 A
Number of Phases	3 phase
Mounting Space	63 in (1600.2 mm)
Bus Material	Copper: busbar
Enclosure Material	Painted steel
Tightening torque	335.97 lbf.in (37.96 N.m) (2/0 AWG...500 kcmil)

Environment

Standards	cULus

Ordering and shipping details

Category	US1PE1A00016
Discount Schedule	PE1A
GTIN	785901475842
Returnability	Yes
Country of origin	US

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	9.250 in (23.495 cm)
Package 1 Width	30.400 in (77.216 cm)
Package 1 Length	51.10 in (129.79 cm)
Package weight(Lbs)	101.999 lb(US) (46.266 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	3
Package 2 Height	32.500 in (82.550 cm)
Package 2 Width	44.500 in (113.030 cm)
Package 2 Length	62.000 in (157.480 cm)
Package 2 Weight	420.0008 lb(US) (190.509 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**893 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**236 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**255 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0.1 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**328 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**75 kg CO2 eq.**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
SCIP Number	**081b184c-7ea7-46e0-b71b-4bab161f6657**
EU RoHS Directive	**Compliant By Exemption**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**
PVC free	**Yes**

Use Again

Repack and remanufacture

Recyclability potential, in %	**67**
Circularity Profile	**No need of specific recycling operations**
Take-back	**No**