

# Product data sheet

Specifications

SQUARE D



Mini circuit breaker, Homeline, 15A, 1 pole, 120VAC, 10kA AIR, combo arc fault, pigtail neutral, plug in, UL

HOM115CAFI

**Product availability:** Stock - Normally stocked in distribution facility

## Main

Product	Miniature circuit-breaker
Range	Homeline
Current Rating	15 A
Certifications	UL Listed
Voltage Rating	120 V AC
Mounting Type	Plug-in
Number of Poles	1P
Short Circuit Current Rating	10 kA
Number of Spaces	1
Circuit Breaker Type	Combination ARC-fault
Ratings	HACR rated
Electrical Connection	Screw clamp terminals
Wire Size	1 x AWG 14...AWG 8 ( aluminium/copper )

## Complementary

Connections - Terminals	Pigtail neutral
Tightening torque	35.4 lbf.in (4.0 N.m) 0.004...0.009 in <sup>2</sup> (2.5...6 mm <sup>2</sup> ) (AWG 14...AWG 8)
Height	3.13 in (79.50 mm)
Width	1 in (25.4 mm)
Depth	2.98 in (75.69 mm)

## Environment

Ambient Air Temperature for Operation	104 °F (40 °C)
---------------------------------------	----------------

## Ordering and shipping details

Category	US1DE3D06301
Discount Schedule	DE3D
GTIN	785901439721
Returnability	Yes
Country of origin	MX

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

## Packing Units

---

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.300 in (3.302 cm)
Package 1 Width	4.00 in (10.16 cm)
Package 1 Length	5.50 in (13.97 cm)
Package weight(Lbs)	10.400 oz (294.835 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	38
Package 2 Height	3.900 in (9.906 cm)
Package 2 Width	13.900 in (35.306 cm)
Package 2 Length	20.800 in (52.832 cm)
Package 2 Weight	24.851 lb(US) (11.272 kg)

## Contractual warranty

---

Warranty Lifetime



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg CO<sub>2</sub> eq, Total Life cycle) **41**

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **Yes**

[EU RoHS Directive](#) **Compliant with Exemptions**

California proposition 65 **WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](#)**

Halogen content performance **Halogen free product**

## Use Again


### Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back **No**

## Technical Illustration

## Dimensions



All dimensions are approximate.  
Also refer to technical drawings and/or documentation.

Image of product / Alternate images

Alternative

---



Market-leading circuit protection



Qwik-Open™ technology - Overload and Short circuit protection

