

Product data sheet

Specifications

SQUARE D



Mini circuit breaker, Homeline, 15A, 1 pole, 120VAC, 10kA AIR, ground fault class A, plug in, UL [TAA]

HOM115GFI

Product availability: Stock - Normally stocked in distribution facility

Main

Product	Miniature circuit-breaker
Range	Homeline
Current Rating	15 A
Certifications	UL Listed
Voltage Rating	120 V AC
Mounting Type	Plug-in
Number of Poles	1P
Short Circuit Current Rating	10 kA
Number of Spaces	1
Circuit Breaker Type	Ground fault protecting class A 6 mA
Ratings	HACR rated
Electrical Connection	Screw clamp terminals
Wire Size	1 x AWG 14...AWG 10 (aluminium/copper)

Complementary

Tightening torque	36.3 lbf.in (4.1 N.m) 0.004...0.009 in ² (2.5...6 mm ²) (AWG 14...AWG 10)
Height	3.13 in (79.50 mm)
Width	1 in (25.4 mm)
Depth	2.98 in (75.69 mm)

Environment

Ambient Air Temperature for Operation	104 °F (40 °C)
---------------------------------------	----------------

Ordering and shipping details

Category	US1DE3D00063
Discount Schedule	DE3D
GTIN	785901065364
Returnability	Yes
Country of origin	MX

Packing Units

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	3.900 in (9.906 cm)
Package 1 Width	5.400 in (13.716 cm)
Package 1 Length	1.300 in (3.302 cm)
Package weight(Lbs)	9.760 oz (276.691 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	38
Package 2 Height	4.100 in (10.414 cm)
Package 2 Width	14.000 in (35.560 cm)
Package 2 Length	21.000 in (53.340 cm)
Package 2 Weight	23.841 lb(US) (10.814 kg)
Unit Type of Package 3	PAL
Number of Units in Package 3	1824
Package 3 Height	40.000 in (101.600 cm)
Package 3 Width	40.000 in (101.600 cm)
Package 3 Length	48.000 in (121.920 cm)
Package 3 Weight	1145.0004 lb(US) (519.363 kg)

Contractual warranty

Warranty	Lifetime
-----------------	----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

 Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	41
Environmental Disclosure	Product Environmental Profile

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
REACH Regulation	REACH Declaration
California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
Halogen content performance	Halogen free product

Use Again

 Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative

Technical Benefits GFCI Circuit Breaker



- 

Protects against overloads and short-circuits
- 

Compatible with Homeline electrical panels and CSEDs with 1 spaces
- 

Product characteristics conformity is certified by the Underwriters Laboratories (UL)
- 

The current capacity that this circuit breaker is able to interrupt before breaking is 10kA
- 

Protection from overload, short-circuit, and Class A Ground Fault
- 

For residential/ commercial use to protect entire branch circuits