

Product data sheet

Specifications

SQUARE D



Safety switch, heavy duty, non fusible, 30A, 600VAC, 600VDC, 3 poles, 30hp, NEMA 12K, Crouse-Hinds Arktite

HU361AWC

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Product	Receptacle Switch
For Use With	Plug APJ3485 Crouse-Hinds Arktite
Disconnect Type	Non-fusible disconnect switch
Number of Poles	3
Current rating	30 A
Voltage Rating	600 V AC 250 V DC
Enclosure Rating NEMA 3R	NEMA 12K
Maximum Horse Power Rating	20 hp at 480 V AC 50-60 Hz for 3 phase motors 30 hp at 600 V AC 50-60 Hz for 3 phase motors 5 hp at 250 V DC

Complementary

Mounting Type	Surface
Electrical Connection	Receptacle
Wire Configuration	4-wire
Wire Size	12 AWG...2 AWG aluminium 14 AWG...2 AWG copper
Tightening torque	45 lbf.in (5.08 N.m) (6 AWG) 40 lbf.in (4.5 N.m) (8 AWG) 35 lbf.in (4.0 N.m) (14 AWG...10 AWG)
Depth	7 in (177.8 mm)
Width	10.5 in (266.7 mm)
Height	16.5 in (419.1 mm)

Environment

Certifications	UL Listed
----------------	-----------

Ordering and shipping details

Category	US10DE100118
Discount Schedule	0DE1
GTIN	785901077763
Returnability	No
Country of origin	US

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	16.875 in (42.862 cm)
Package 1 Width	5.250 in (13.335 cm)
Package 1 Length	7.50 in (19.05 cm)
Package weight(Lbs)	22.000 lb(US) (9.979 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	85 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	54 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	3 kg CO2 eq.
Carbon footprint of the installation phase [A5]	1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	3 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	23 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	Fcbb2f4b-148e-498d-b15c-530db69350d4
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	89
Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.