

Product data sheet

Specifications

SQUARE D



Safety switch, heavy duty, non fusible, 200A, 3 pole, 150HP, 600V AC/DC, NEMA 4X, fiberglass reinforced polyester

HU364DF

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Product	Single Throw Safety Switch
Duty Rating	Heavy duty
Device Application	Heavy application
Disconnect Type	Non-fusible disconnect
Factory Installed Neutral	None
Number of Poles	3
Current Rating	200 A
Voltage Rating	600 V AC/DC
Enclosure Rating	NEMA 4X fiberglass reinforced polyester
Motor power hp	125 hp at 480 V AC 50-60 Hz for 3 phase motors 150 hp at 600 V AC 50-60 Hz for 3 phase motors 50 hp at 600 V DC

Complementary

Mounting Type	Surface
Electrical Connection	Lugs
Wiring configuration	3-wire
Wire Size	AWG 6...250 kcmil copper or aluminium
Tightening torque	275 lbf.in (31.07 N.m) 0.02...0.2 in ² (13.3...127 mm ²) (AWG 6...250 kcmil)
Depth	11.8 in (299.7 mm)
Width	31.3 in (795.02 mm)
Height	26.3 in (668.02 mm)
Net Weight	89.0007 lb(US) (40.37 kg)

Environment

Certifications	UL listed file E2875 CSA
----------------	-----------------------------

Ordering and shipping details

Category	US10DE100111
Discount Schedule	0DE1
GTIN	785901627937

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Returnability	Yes
----------------------	-----

Country of origin	MX
--------------------------	----

Packing Units

Unit Type of Package 1	PCE
-------------------------------	-----

Nbr. of units in pkg.	1
------------------------------	---

Package 1 Height	16.00 in (40.64 cm)
-------------------------	---------------------

Package 1 Width	27.00 in (68.58 cm)
------------------------	---------------------

Package 1 Length	35.00 in (88.9 cm)
-------------------------	--------------------

Package weight(Lbs)	89.0007 lb(US) (40.37 kg)
----------------------------	---------------------------

Contractual warranty

Warranty	18 months
-----------------	-----------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) **352**

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **No**

[EU RoHS Directive](#) **Compliant**

California proposition 65 **WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

PVC free **Yes**

Use Again

Repack and remanufacture

Circularity Profile **No need of specific recycling operations**

Take-back **No**