

# Product data sheet

Specifications

SQUARE D



Safety switch, heavy duty, non fusible, 400A, 3 wire, 3 pole, 350HP, 600V AC/DC, NEMA 4, 4X, 5, 304 stainless steel

HU365DS

Product availability: Stock - Normally stocked in distribution facility

## Main

|                             |  |
|-----------------------------|--|
| Product                     | Single Throw Safety Switch   |
| Duty Rating                 | Heavy duty   |
| Device Application          | Heavy application  |
| Disconnect Type             | Non-fusible disconnect   |
| Factory Installed Neutral   | None   |
| Number of Poles             | 3  |
| Current Rating              | 400 A  |
| Voltage Rating              | 600 V AC/DC  |
| Enclosure Rating            | NEMA 4/4X/5 stainless steel 304  |
| Standard Motor Power Rating | 125 hp at 240 V AC 50-60 Hz for 3 phase motors<br>250 hp at 480 V AC 50-60 Hz for 3 phase motors<br>350 hp at 600 V AC 50-60 Hz for 3 phase motors<br>50 hp at 250 V DC<br>50 hp at 600 V DC |

## Complementary

|                       |   |
|-----------------------|---|
| Mounting Type         | Surface                                     |
| Electrical Connection | Lugs  |
| Wiring configuration  | 3-wire                                      |
| Wire Size             | AWG 1/0...750 kcmil copper or aluminium     |
| Tightening torque     | 550 lbf.in (62.1 N.m) (AWG 1/0...750 kcmil) |
| Depth                 | 10.13 in (257.30 mm)                        |
| Width                 | 26.25 in (666.75 mm)                        |
| Height                | 46.25 in (1174.75 mm)                       |
| Net Weight            | 170.0 lb(US) (77.1 kg)                      |

## Environment

|                |                      |
|----------------|----------------------|
| Certifications | UL listed file E2875 |
|----------------|----------------------|

## Ordering and shipping details

|                   |              |
|-------------------|--------------|
| Category          | US10DE100055 |
| Discount Schedule | 0DE1         |
| GTIN              | 785901195979 |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

|               |     |
|---------------|-----|
| Returnability | Yes |
|---------------|-----|

## Packing Units

---

|                        |     |
|------------------------|-----|
| Unit Type of Package 1 | PCE |
|------------------------|-----|

---

|                       |   |
|-----------------------|---|
| Nbr. of units in pkg. | 1 |
|-----------------------|---|

---

|                  |                   |
|------------------|-------------------|
| Package 1 Height | 13.0 in (33.0 cm) |
|------------------|-------------------|

---

|                 |                     |
|-----------------|---------------------|
| Package 1 Width | 27.008 in (68.6 cm) |
|-----------------|---------------------|

---

|                  |                    |
|------------------|--------------------|
| Package 1 Length | 51.5 in (130.8 cm) |
|------------------|--------------------|

---

|                     |                             |
|---------------------|-----------------------------|
| Package weight(Lbs) | 175.0009 lb(US) (79.379 kg) |
|---------------------|-----------------------------|

## Contractual warranty

---

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

|  <b>Environmental footprint</b> |   |
|--|---|
| Carbon footprint (kg CO2 eq, Total Life cycle)   | 1346  |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a> |

### Use Better

|  <b>Materials and Substances</b> |  |
|---|--|
| Packaging made with recycled cardboard  | Yes  |
| Packaging without single use plastic  | Yes  |
| <a href="#">EU RoHS Directive</a>   | Compliant with Exemptions  |
| REACH Regulation  | <a href="#">REACH Declaration</a>  |
| California proposition 65   | <b>WARNING:</b> This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| Halogen content performance   | Halogen free plastic parts product   |
| PVC free  | Yes  |


### Use Again

|  <b>Repack and remanufacture</b> |  |
|---|--|
| Circularity Profile   | No need of specific recycling operations |
| Take-back   | No                                       |

Technical Illustration

Dimensions

---




Technical Illustration

Wiring diagram

---

NOT FUSIBLE



HU365AWK

HU365DS

HU365SS