



Main

Circuit Breaker Type	JGL JDL
Breaker Compatibility	Circuit breaker J-Frame 2P Circuit breaker J-Frame 3P

Complementary

Rated Current	150...250 A
Poles Description	2P 3P
Enclosure Material	Cast Aluminium
Height	22.72 in (577 mm)
Width	10.9 in (278 mm)
Depth	7.7 in (196 mm)

Environment

Product Certifications	CSA[RETURN]UL
------------------------	---------------

Environmental

NEMA Degree of Protection	NEMA 7
---------------------------	--------

Ordering and shipping details

Category	US10DE100031
Discount Schedule	ODE1
GTIN	3606486279410
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	36.901 lb(US) (16.738 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty	18 months
----------	-----------