

# Product data sheet

Specifications

SQUARE D



## Automatic switch, PowerPact L, 400A, 3 pole, 600VAC, 50kA, lugs, magnetic

LLL36000S40X

Product availability: Stock - Normally stocked in distribution facility

### Main

Product or Component Type	Automatic switch
Range of Product	PowerPact L
Trip unit technology	Magnetic
Circuit breaker type	L-Frame

### Complementary

Line Rated Current	400 A
[Ue] rated operational voltage	600 V AC
Mounting Mode	Unit mount
Poles description	3P
Short-circuit withstand	125 kA 240 V UL 489 100 kA 480 V UL 489 50 kA 600 V UL 489
Breaking capacity code	L
Electrical connection	Lugs, line Lugs, load
AWG gauge	x AWG 2/0...500 kcmil ( aluminium/copper )
Terminal identifier	AL600LS52K3
Magnetic tripping current	4800 A
Height	13.38 in (339.85 mm)
Width	5.51 in (139.95 mm)
Depth	6.61 in (167.89 mm)
Tightening torque	442.5 lbf.in (50 N.m) 0.1...0.4 in <sup>2</sup> (70...240 mm <sup>2</sup> ) (AWG 2/0...500 kcmil)

### Environment

Product Certifications	CSA IEC UL Listed
------------------------	-------------------------

### Ordering and shipping details

Category	US10DE201116
Discount Schedule	0DE2
GTIN	785901731689
Returnability	Yes

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

Country of origin	MX
-------------------	----

## Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

---

Nbr. of units in pkg.	1
-----------------------	---

---

Package 1 Height	8.750 in (22.225 cm)
------------------	----------------------

---

Package 1 Width	10.750 in (27.305 cm)
-----------------	-----------------------

---

Package 1 Length	19.50 in (49.53 cm)
------------------	---------------------

---

Package weight(Lbs)	15.0003 lb(US) (6.804 kg)
---------------------	---------------------------

## Contractual warranty

---

Warranty	18 months
----------	-----------



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 796

Environmental Disclosure [Product Environmental Profile](#)

### Use Better

#### Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

REACH Regulation [REACH Declaration](#)

California proposition 65 **WARNING:** This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

PVC free Yes

### Use Again

#### Repack and remanufacture


Circularity Profile [End of Life Information](#)

Take-back No

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Technical Illustration

Dimensions



All dimensions are approximate.  
 Also see CAD, technical drawings, and technical documentation.