



## Main

Range of product	Multi9
Product or Component Type	Shunt trip release with OC contact
Device short name	MX + OF
Signal contacts composition	1 C/O
Line Rated Current	6 A at <= 240 V, AC
[Uc] control circuit voltage	12...24 V AC 50/60 Hz 12...24 V DC
9 mm pitches	2

## Complementary

Range compatibility	Multi 9 Multi9 C60 C60BP Multi 9 Multi9 C60 C60BPR Multi 9 Multi9 C60 C60SP Multi 9 Multi9 GFP GFP Multi 9 Multi9 C60H-DC C60H-DC
Local signalling	Action indicator
Mounting Mode	Fixed
Mounting Support	DIN rail
Height	3.2 in (82.5 mm)
Width	0.7 in (18 mm)
Depth	2.7 in (68 mm)
Net Weight	0.143 lb(US) (0.065 kg)
Connections - terminals	Clamp terminal bottom) - 1 0.004 in <sup>2</sup> (2.5 mm <sup>2</sup> ) AWG 14) - rigid Clamp terminal bottom) - 2 0.002 in <sup>2</sup> (1.5 mm <sup>2</sup> ) AWG 16) - rigid
Wire stripping length	0.4 in (9 mm) for bottom connection
Tightening torque	8.9 lbf.in (1 N.m) bottom

## Environment

Standards	EN/IEC 60947-1 EN/IEC 60947-5-1
Product Certifications	CCC[RETURN]PCT[RETURN]JUL[RETURN]JUR
Pollution degree	3
Ambient Air Temperature for Operation	-13...122 °F (-25...50 °C)
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)

## Ordering and shipping details

Category	US10DE200948
Discount Schedule	0DE2
GTIN	3606480639098
Returnability	Yes
Country of origin	US

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.2 in (3 cm)
Package 1 Width	3.1 in (8 cm)
Package 1 Length	3.7 in (9.4 cm)
Package 1 Weight	2.6 oz (75 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	3.4 in (8.6 cm)
Package 2 Width	3.9 in (10 cm)
Package 2 Length	10.4 in (26.5 cm)
Package 2 Weight	23.3 oz (660 g)
Unit Type of Package 3	S03
Number of Units in Package 3	72
Package 3 Height	11.8 in (30 cm)
Package 3 Width	11.8 in (30 cm)
Package 3 Length	15.7 in (40 cm)
Package 3 Weight	14.158 lb(US) (6.422 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.