



Unit Substation, Mini Power-Zone, 1 Phase, 5kVA, 480V Pri, 120/240V Sec, Type 3R, 18kA, wall mounted, bolt on branch

MPUB5S40F

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 4,860.00 USD

Main

Certifications	UL Listed
Туре	Mini Power-Zone
Phase	1 phase
Primary Voltage	480 V
Secondary Voltage	120/240 V
Full Capacity Taps	2 5 % FCBN
Power Rating	5 kVA
Temperature Rise	115 °C
Winding Material	Copper
Interrupt Rating	18 kA
Interior Type	NQ Panelboard interior
Number of Spaces Available	16.0
Number of Circuits	16.0
Enclosure Type	NEMA 3R hot-rolled steel

Complementary

	-
Height	43.20 in (1097.28 mm)
Width	16.0000000000 in (406.4 mm)
Depth	11.75 in (298.45 mm)
Product Weight	186.97 lb(US) (84.81 kg)

Ordering and shipping details

Category	US10PE216275
Discount Schedule	0PE2
GTIN	3606487189527
Returnability	No
Country of origin	US

Packing Units

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.81 in (30.0 cm)
Package 1 Width	16.06 in (40.8 cm)
Package 1 Length	43.23 in (109.8 cm)
Package 1 Weight	224.9 lb(US) (102.0 kg)

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
China RoHS Regulation	China RoHS declaration

Use Again

○ Repack and remanufacture		
Take-back	No	