



Panelboard interior, NF, main lugs, 400A, Cu bus, 66 pole spaces, 3 phase, 4 wire, 600Y/347VAC max

NF466L4C

Product availability: Stock - Normally stocked in distribution facility

Main

| Panelboard Type | Main lugs |
|-----------------------------|-------------|
| Branch Circuit Breaker Type | EDB/EDG/EDJ |
| Busbar Material | Copper |

Complementary

| Number of spaces | 66 | |
|--------------------------------|---|--|
| Enclosure Nominal Height | 74 in (1879.6 mm) 86 in (2184.4 mm) | |
| Enclosure Nominal Width | 20 in (508 mm) | |
| Enclosure Nominal Depth | 5.75 in (146.05 mm) NEMA 1 6.5 in (165.1 mm) NEMA 3R/5/12 | |
| Line Rated Current | 400 A | |
| [lu] rated interrupted current | 65 kA | |
| Number of Phases | 3 phase 4 wires | |
| Voltage Rating | 600Y/347 V AC | |
| Connections - terminals | Lug line AWG 1/0750 kcmil aluminium Lug neutral AWG 1/0750 kcmil aluminium | |
| Tightening torque | 274.99300.04 lbf.in (31.0733.90 N.m) 0.080.6 in² (53.48380 mm²) (AWG 1/0750 kcmil) 274.99300.04 lbf.in (31.0733.90 N.m) 0.080.3 in² (53.48177.3 mm²) (AWG 1/0350 kcmil) 549.98 lbf.in (62.14 N.m) 0.080.6 in² (53.48380 mm²) (AWG 1/0750 kcmil) 549.98 lbf.in (62.14 N.m) 0.080.2 in² (53.48152 mm²) (AWG 1/0300 kcmil) 375.006 lbf.in (42.37 N.m) 0.080.6 in² (53.48380 mm²) (AWG 1/0750 kcmil) 375.006 lbf.in (42.37 N.m) 0.080.2 in² (53.48152 mm²) (AWG 1/0300 kcmil) | |
| Height | 48 in (1219.2 mm) | |
| Width | 10.44 in (265.18 mm) | |
| Net Weight | 45.00 lb(US) (20.41 kg) | |

Environment

| Standards | CSA C22.2 |
|-----------|-----------|
| | UL 67 |

Ordering and shipping details

| Category | US1PE1A08350 | |
|-------------------|--------------|--|
| Discount Schedule | PE1A | |
| GTIN | 785901344995 | |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Returnability | Yes |
|-------------------|-----|
| Country of origin | MX |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------|---------------------------|
| Nbr. of units in pkg. | 1 |
| Package 1 Height | 73.25 in (186.055 cm) |
| Package 1 Width | 6.00 in (15.24 cm) |
| Package 1 Length | 13.63 in (34.608 cm) |
| Package weight(Lbs) | 44.000 lb(US) (19.958 kg) |

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

| ⊘ Environmental footprint | | |
|--|-----|--|
| Carbon footprint (kg CO2 eq, Total Life cycle) | 394 | |

Use Better

| Materials and Substances | |
|--|---|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | No |
| EU RoHS Directive | Compliant |
| REACh Regulation | REACh Declaration |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |

Use Again

| ○ Repack and remanufacture | |
|----------------------------|--|
| Circularity Profile | No need of specific recycling operations |
| Take-back | No |