QO2100C

Mini circuit breaker, QO, 100A, 2 pole, 120/240VAC, 10kA, plug in, clam





Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	100 A
Voltage Rating	120/240 V AC 120 V AC
Mounting Type	Plug-in
Number of Poles	2P
Circuit Breaker Type	Standard
Ratings	HACR rated
Electrical Connection	Box lugs
Type of Packing	Clam packaging

Complementary

Complementary		
Interrupt Rating	10 KA 120/240 V AC 10 kA 120 V AC	
Number of Panel Spaces	2	
Wire Size	AWG 4AWG 2/0 copper or aluminium	
Tightening Torque	49.6 lbf.in (5.6 N.m)	
Height	3.5 in (89 mm)	
Width	1.5 in (38 mm)	
Depth	2.9 in (74 mm)	
Net Weight	0.750 lb(US) (0.340 kg)	

Environment

Certifications	UL Listed[RETURN]CSA
Ambient Rating	104 °F (40 °C)

Ordering and shipping details

Category	US1CP1021756	
Discount Schedule	CP10	
GTIN	785901691235	
Returnability	Yes	
Country of origin	US	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	1.600 in (4.064 cm)	
Package 1 Width	4.50 in (11.43 cm)	
Package 1 Length	4.800 in (12.192 cm)	
Package 1 Weight	12.000 oz (340.194 g)	
Unit Type of Package 2	CAR	
Number of Units in Package 2	3	
Package 2 Height	5.200 in (13.208 cm)	
Package 2 Width	5.200 in (13.208 cm)	

4.900 in (12.446 cm)	
2.350 lb(US) (1.066 kg)	
PAL	
960	-
40.0000000000 in (101.6 cm)	
40.0000000000 in (101.6 cm)	
48.0000000000 in (121.92 cm)	
758.999 lb(US) (344.276 kg)	
	2.350 lb(US) (1.066 kg) PAL 960 40.0000000000 in (101.6 cm) 40.0000000000 in (101.6 cm) 48.0000000000 in (121.92 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Cadmium and cadmium compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	€Yes
Circularity Profile	No need of specific recycling operations
Halogen content performance	Halogen free product