



Mini circuit breaker, QO, 20A, 2 pole, 120/240VAC, 10kA, plug in, ring

QO2205237

Product availability: Stock - Normally stocked in distribution facility

### Main

| Product               | Miniature circuit-breaker |  |
|-----------------------|---------------------------|--|
| Range                 | QO                        |  |
| Current Rating        | 20 A                      |  |
| Voltage Rating        | 120/240 V AC<br>120 V AC  |  |
| Mounting Type         | Plug-in                   |  |
| Number of Poles       | 2P                        |  |
| Circuit Breaker Type  | Standard                  |  |
| Ratings               | HACR rated                |  |
| Electrical Connection | Ring tongue               |  |

## Complementary

| Interrupt Rating       | 10 kA 120/240 V AC<br>10 kA 120 V AC |  |
|------------------------|--------------------------------------|--|
| Number of Panel Spaces | 3                                    |  |
| Wire Size              | AWG 14AWG 8 copper or aluminium      |  |
| Tightening Torque      | 35.4 lbf.in (4 N.m)                  |  |
| Height                 | 3.0 in (76 mm)                       |  |
| Width                  | 1.5 in (38 mm)                       |  |
| Depth                  | 2.9 in (74 mm)                       |  |
| Net Weight             | 0.509 lb(US) (0.231 kg)              |  |

## **Environment**

| Certifications | UL Listed<br>CSA |
|----------------|------------------|
| Ambient Rating | 104 °F (40 °C)   |

## Ordering and shipping details

| Category          | US1DE2A00004 |
|-------------------|--------------|
| Discount Schedule | DE2A         |
| GTIN              | 785901933083 |
| Returnability     | Yes          |
| Country of origin | MX           |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

# **Packing Units**

| Unit Type of Package 1 | PCE                  |
|------------------------|----------------------|
| Nbr. of units in pkg.  | 1                    |
| Package 1 Height       | 1.60 in (4.064 cm)   |
| Package 1 Width        | 3.40 in (8.636 cm)   |
| Package 1 Length       | 3.50 in (8.89 cm)    |
| Package weight(Lbs)    | 8.160 oz (231.332 g) |

## **Contractual warranty**

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

| ∇ Environmental footprint                      |                               |
|--|-------------------------------|
| Carbon footprint (kg CO2 eq, Total Life cycle) | 19                            |
| Environmental Disclosure                       | Product Environmental Profile |

#### **Use Better**

| Packaging made with recycled cardboard | No                                   |
|--|--------------------------------------|
| Packaging without single use plastic   | Yes                                  |
| EU RoHS Directive                      | Compliant                            |
| SCIP Number                            | Af42fb01-813d-40c0-ae28-b8b3299dbc99 |
| REACh Regulation                       | REACh Declaration                    |
| Halogen content performance            | Halogen free product                 |

## **Use Again**

| ○ Repack and remanufacture |  |
|----------------------------|--|
| Circularity Profile        | No need of specific recycling operations |
| Take-back                  | No                                       |

## **Technical Illustration**

## **Dimensions**

