

# Product data sheet

Specifications

SQUARE D



Mini circuit breaker, QO, 15A, 3 pole, 120/240VAC, 10kA, plug in, ring

QO3155237

Product availability: Stock - Normally stocked in distribution facility

## Main

|                       |                                      |
|-----------------------|--------------------------------------|
| Product               | Miniature circuit-breaker            |
| Range                 | QO                                   |
| Current Rating        | 15 A                                 |
| Voltage Rating        | 120/240 V AC<br>240 V AC<br>120 V AC |
| Mounting Type         | Plug-in                              |
| Number of Poles       | 3P                                   |
| Circuit Breaker Type  | Standard                             |
| Ratings               | HACR rated                           |
| Electrical Connection | Ring tongue                          |

## Complementary

|                        |  |
|------------------------|--|
| Interrupt Rating       | 10 kA 120/240 V AC<br>10 kA 240 V AC<br>10 kA 120 V AC |
| Number of Panel Spaces | 3  |
| Wire Size              | AWG 14...AWG 8 copper or aluminium                     |
| Tightening Torque      | 35.4 lbf.in (4 N.m)                                    |
| Height                 | 3.0 in (76 mm)   |
| Width                  | 2.2 in (57 mm)   |
| Depth                  | 2.9 in (74 mm)   |
| Net Weight             | 0.611 lb(US) (0.277 kg)                                |

## Environment

|                |                  |
|----------------|------------------|
| Certifications | UL Listed<br>CSA |
| Ambient Rating | 104 °F (40 °C)   |

## Ordering and shipping details

|                   |              |
|-------------------|--------------|
| Category          | US1DE2A00004 |
| Discount Schedule | DE2A         |
| GTIN              | 785901420712 |
| Returnability     | Yes          |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

Country of origin MX

## Packing Units

---

|                        |                      |
|------------------------|----------------------|
| Unit Type of Package 1 | PCE                  |
| Nbr. of units in pkg.  | 1                    |
| Package 1 Height       | 2.30 in (5.842 cm)   |
| Package 1 Width        | 3.50 in (8.89 cm)    |
| Package 1 Length       | 3.70 in (9.398 cm)   |
| Package weight(Lbs)    | 9.760 oz (276.691 g) |

## Contractual warranty

---

Warranty 18 months



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg CO<sub>2</sub> eq, Total Life cycle) **19**

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard **No**

Packaging without single use plastic **Yes**

[EU RoHS Directive](#) **Compliant**

SCIP Number [Af42fb01-813d-40c0-ae28-b8b3299dbc99](#)

REACH Regulation [REACH Declaration](#)

California proposition 65  
WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](#)

Halogen content performance **Halogen free product**

## Use Again

### Repack and remanufacture

Circularity Profile **No need of specific recycling operations**

Take-back **No**

## Technical Illustration

## Dimensions

