

Product data sheet

Specifications

SQUARE D



Load center, QO, 3 phase, 3 spaces, 3 circuits, 60A main lugs, NEMA1, neutral gnd bar, flush cover

QO403L60NF

Product availability: Stock - Normally stocked in distribution facility

Main

Marketing Trade Name	QO
Product Type	Load Center
Cover Type	Flush cover

Complementary

Tightening Torque	Main lugs 35 lb.in, AWG 14...AWG 10, aluminium/copper Main lugs 50 lb.in, AWG 3...AWG 1, aluminium/copper Main lugs 40 lb.in, AWG 8...AWG 4, aluminium/copper Main lugs 35 lb.in, AWG 12...AWG10, aluminium/copper
PoN Convertible Mains (lugs)	Fixed Mains (lugs)
Rated Current	60 A
Number of Spaces	3
Max Short Circuit Current Rating	65 kA
Maximum Number of Single Pole Circuits	3
Maximum Number of Tandem Breakers	0
Number of Phases	3 phase 4 wires
Voltage Rating	208Y/120 V AC 240/120 V delta AC 240 V delta AC
Wire Size	AWG 10...AWG 6 copper
Ground Bar	Neutral (factory installed)
Electrical Connection	Lugs
Busbar Material	Tin plated aluminium: busbar
Enclosure Material	Welded sheet steel
Surface Finish	Baked enamel Gray
Box Number	13
Height	13.1 in (333 mm)
Width	5.9 in (149 mm)
Depth	3.4 in (86 mm)
Net Weight	6.173 lb(US) (2.800 kg)

Environment

Enclosure Rating	NEMA 1 indoor enclosure
------------------	-------------------------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)
Product Certifications	UL Listed

Ordering and shipping details

Category	US10DE300011
Discount Schedule	ODE3
GTIN	785901051695
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	3.80 in (9.652 cm)
Package 1 Width	7.60 in (19.304 cm)
Package 1 Length	15.00 in (38.100 cm)
Package weight(Lbs)	5.800 lb(US) (2.631 kg)

Contractual warranty

Warranty	18 months
----------	-----------



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

EU RoHS Directive Under investigation

REACH Regulation [REACH Declaration](#)

California proposition 65 WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

Repack and remanufacture

Circularity Profile No need of specific recycling operations

Take-back No