

# Product data sheet

Specifications

SQUARE D



Load center, QO, 3 phase, 3 spaces, 3 circuits, 60A main lugs, NEMA3R, neutral gnd bar

QO403L60NRB

Product availability: Stock - Normally stocked in distribution facility

## Main

Marketing Trade Name	QO
Product Type	Load Center
Cover Type	Surface cover

## Complementary

Tightening Torque	Main lugs 35 lb.in, AWG 14...AWG 10, aluminium/copper Main lugs 50 lb.in, AWG 3...AWG 1, aluminium/copper Main lugs 40 lb.in, AWG 8...AWG 4, aluminium/copper Main lugs 35 lb.in, AWG 12...AWG10, aluminium/copper
PoN Convertible Mains (lugs)	Fixed Mains (lugs)
Rated Current	60 A
Number of Spaces	3
Max Short Circuit Current Rating	65 kA
Maximum Number of Single Pole Circuits	3
Maximum Number of Tandem Breakers	0
Number of Phases	3 phase 4 wires
Voltage Rating	208Y/120 V AC 240/120 V delta AC 240 V delta AC
Wire Size	AWG 10...AWG 6 copper
Ground Bar	Grounding bar (ordered separately)
Electrical Connection	Lugs
Busbar Material	Tin plated aluminium: busbar
Enclosure Material	Welded galvannealed steel
Surface Finish	Baked enamel Gray
Box Number	10R
Height	13.2 in (335 mm)
Width	6.9 in (176 mm)
Depth	4.1 in (105 mm)
Net Weight	9.259 lb(US) (4.200 kg)

## Environment

Enclosure Rating	NEMA 3R weatherproof enclosure
------------------	--------------------------------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)
Product Certifications	UL Listed

---

## Ordering and shipping details

---

Category	US10DE300017
Discount Schedule	ODE3
GTIN	785901051718
Returnability	Yes
Country of origin	MX

---

## Packing Units

---

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	5.12 in (13.0 cm)
Package 1 Width	8.39 in (21.3 cm)
Package 1 Length	15.00 in (38.1 cm)
Package weight(Lbs)	8.11 lb(US) (3.68 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	105
Package 2 Height	40.00 in (101.6 cm)
Package 2 Width	40.00 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)
Package 2 Weight	860.77 lb(US) (390.44 kg)

---

## Contractual warranty

---

Warranty	18 months
----------	-----------



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

## Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

EU RoHS Directive Under investigation

REACH Regulation [REACH Declaration](#)

California proposition 65 WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## Use Again

### Repack and remanufacture

Circularity Profile No need of specific recycling operations

Take-back No