



Load center accessory, QO, mounting base, 1 phase, 30 spaces, 200A main lugs, PoN, double lugs, OEM

QON130L200PDL

Product availability: Stock - Normally stocked in distribution facility

### Main

Product Type	Mounting base	
Marketing Trade Name	QO	
Load Center Type	PoN Convertible Mains (lugs)	
Rated Current	200 A	
Number of Spaces	30	
Max Short Circuit Current Rating	10 kA	
Number of Phases	1 phase 3 wires	
Voltage Rating	120/240 V AC	

# Complementary

Wire Size	AWG 4300 kcmil aluminium/copper	
Height	17.2 in (438 mm)	
Width	10.6 in (270 mm)	
Depth	2.6 in (66 mm)	
Net Weight	3.0005 lb(US) (1.361 kg)	

#### **Environment**

Ambient Air Temperature for	39 °C (103 °F)	
Operation	-5 °C (23 °F)	

## Ordering and shipping details

Category	US1DE3A00909	
Discount Schedule	DE3A	
GTIN	785901451716	
Returnability	Yes	
Country of origin	US	

## **Packing Units**

Unit Type of Package 1	PCE	
Nbr. of units in pkg.	1	
Package 1 Height	17.24 in (43.8 cm)	
Package 1 Width	10.63 in (27.0 cm)	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Package 1 Length	2.68 in (6.8 cm)	
Package weight(Lbs)	4.149 lb(US) (1.882 kg)	



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

#### **Use Better**

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

### Use Again

○ Repack and remanufacture	
Take-back	No