



Mini circuit breaker, QOU, 30A, 3 pole, 240 VAC, 10kA, removable screw terminal

QOU3305292

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Product or Component Type	Miniature circuit-breaker	
Range of Product	QOU	
Circuit breaker type	Standard	
Circuit breaker application	HACR rated	

Complementary

Line Rated Current	30 A	
Electrical connection	removable screw terminals, line side removable screw terminals, load side	
[Ue] rated operational voltage	120/240 V AC 240 V AC 120 V AC 48 V DC	
Mounting Mode	Unit mount	
Height	4.05 in (102.87 mm)	
Width	3 in (76.2 mm)	
Depth	2.95 in (74.93 mm)	
Tightening torque	45 lbf.in (5.08 N.m) (AWG 14AWG 2)	

Environment

Product Certifications	IEC
	CSA
	10.15 (-)
	UL Listed

Ordering and shipping details

Category	US10DE200900
Discount Schedule	0DE2
GTIN	3606486146972
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.50 in (6.35 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Package 1 Width	3.60 in (9.144 cm)	
Package 1 Length	4.80 in (12.192 cm)	
Package weight(Lbs)	18.560 oz (526.167 g)	

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental Disclosure

Product Environmental Profile

Use Better

Packaging made with recycled cardboard	No
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
SCIP Number	Af42fb01-813d-40c0-ae28-b8b3299dbc99
REACh Regulation	REACh Declaration
Halogen content performance	Halogen free product

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No

Technical Illustration

Dimensions

