



Mini circuit breaker, QOU, 80A, 3 pole, 240 VAC, 10kA, lock-off

QOU3807100

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Product or Component Type	Miniature circuit-breaker	
Range of Product	QOU	
Circuit breaker type	Standard	
Circuit breaker application	HACR rated	

Complementary

Line Rated Current	80 A	
Electrical connection	Slotted box lugs, line side	
	Slotted box lugs, load side	
[Ue] rated operational voltage	120/240 V AC	
	240 V AC	
	120 V AC	
	60 V DC	
Mounting Mode	Unit mount	
AWG gauge	AWG 12AWG 2/0 aluminium/copper	
Height	4.45 in (113.03 mm)	
Width	2.25 in (57.15 mm)	
Depth	2.95 in (74.93 mm)	
Tightening torque	45 lbf.in (5.08 N.m) (AWG 12AWG 2/0)	

Environment

Product Certifications	IEC UL Listed
	CSA

Ordering and shipping details

Category	US10DE200900	
Discount Schedule	0DE2	
GTIN	785901691693	
Returnability	No	
Country of origin	MX	

Packing Units

Unit Type of Package 1	PCE
Nhr of units in nka	1

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Package 1 Height	2.50 in (6.35 cm)
Package 1 Width	3.50 in (8.89 cm)
Package 1 Length	4.80 in (12.192 cm)
Package weight(Lbs)	23.360 oz (662.245 g)

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Environmental Disclosure

Product Environmental Profile

Use Better

Packaging made with recycled cardboard	No
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
SCIP Number	Af42fb01-813d-40c0-ae28-b8b3299dbc99
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Cadmium and cadmium compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Halogen content performance	Halogen free product

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No

Product data sheet

QOU3807100

Technical Illustration

Dimensions

