

Product data sheet

Specifications

SQUARE D



Surge protection device,
SurgeLogic, 36kA, 120 VAC, 1
phase, 3 wire, 25kA SCCR, NEMA
4X

SDSA1175

Product availability: Stock - Normally stocked in distribution facility

Main

Product	Surge protection device
Range	SurgeLogic

Complementary

Voltage Rating	120 V AC
MCOV	150 V
SCCR	25 kA
Surge Current	36 kA
Nominal Discharge Current	10 kA
Number of Phases	1 phase
Wiring Configuration	3-wire
Connection	Wire
Local Signalling	Status LED
Cable length	24 in (609.6 mm)
Height	2.25 in (57.15 mm)
Width	2.25 in (57.15 mm)
Depth	1.935 in (49.149 mm)

Environment

Enclosure Rating	NEMA 4X
Enclosure Material	Black Plastic
Standards	CSA C22.2 No 8 UL 1449.ed. 4

Ordering and shipping details

Category	US1DE1B08462
Discount Schedule	DE1B
GTIN	785901984092
Returnability	Yes
Country of origin	MX

Packing Units

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.600 in (6.604 cm)
Package 1 Width	2.600 in (6.604 cm)
Package 1 Length	6.900 in (17.526 cm)
Package weight(Lbs)	10.400 oz (294.835 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	20
Package 2 Height	7.500 in (19.050 cm)
Package 2 Width	10.800 in (27.432 cm)
Package 2 Length	13.000 in (33.020 cm)
Package 2 Weight	13.889 lb(US) (6.300 kg)

Contractual warranty

Warranty	18 months
-----------------	-----------



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
REACH Regulation	REACH Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov


Use Again

Repack and remanufacture

Take-back	No
-----------	----


Technical Illustration

Dimensions



Technical Illustration

Wiring diagram



LED ON = OK (normal operation)
LED OFF = Loss of Surge Suppression; Refer to Technical Documentation