



Safety switch, VisiPacT, heavy duty, unfused, viewing window, NEMA 12, 600V, 30A, 3 pole, ground lugs, electrical interlock kit

VHU361AWKGLEI

Product availability: Stock - Normally stocked in distribution facility

Main

Product	Single Throw Safety Switch Interlock	
Duty Rating	Heavy duty	
Device Application	Heavy application	
Disconnect Type	Non-fusible disconnect	
Factory Installed Neutral	Field installed kit available	
Number of Poles	3	
Current Rating	30 A	
Voltage Rating	600 V AC/DC	
Enclosure Rating	NEMA 12 galvannealed steel	
Standard Motor Power Rating	5 hp at 240 V AC 50/60 Hz for 1 phase motors 10 hp at 240 V AC 50/60 Hz for 3 phase motors 7.5 hp at 480 V AC 50/60 Hz for 1 phase motors 20 hp at 480 V AC 50/60 Hz for 3 phase motors 10 hp at 600 V AC 50/60 Hz for 1 phase motors 30 hp at 600 V AC 50/60 Hz for 1 phase motors 30 hp at 600 V AC 50/60 Hz for 3 phase motors 5 hp at 250 V DC 15 hp at 600 V DC	

Complementary

Mounting Type	Surface	
Electrical Connection	Lugs	
Wiring configuration	3-wire	
Wire Size	AWG 12AWG 6 aluminium AWG 14AWG 6 copper	
Tightening torque	45 lbf.in (5.08 N.m) 0.02 in² (13.3 mm²) (AWG 6) 40 lbf.in (4.5 N.m) 0.013 in² (8.367 mm²) (AWG 8) 35 lbf.in (4.0 N.m) 0.0030.008 in² (2.065.261 mm²) (AWG 14AWG 10)	
Depth	5.242 in (133.147 mm)	
Width	6.48 in (164.59 mm)	
Height	14.57 in (370.08 mm)	
Net Weight	11.02 lb(US) (5 kg)	
Grounding Kit	Factory installation	
Service Entrance	Suitable service entrance for USA Suitable service entrance for Mexico	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environment

Certifications	UL listed file E2875
Standards	UL98
	CSA C22.2 No 4
	NOM-003-SCFI-2000

Ordering and shipping details

Category	US10DE100113
Discount Schedule	0DE1
GTIN	3606486997345
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	5.404 in (13.726 cm)
Package 1 Width	7.806 in (19.827 cm)
Package 1 Length	17.513 in (44.484 cm)
Package weight(Lbs)	10.401 lb(US) (4.718 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	96
Package 2 Height	44.000 in (111.760 cm)
Package 2 Width	40.000 in (101.600 cm)
Package 2 Length	48.000 in (121.920 cm)
Package 2 Weight	1003.591 lb(US) (455.221 kg)



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	43
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No