

Technical data sheet · LÜTZE SUPERFLEX® N PVC

For high requirements



Identification	Type	SU N PVC 12G1,5
	Part-No.	A1481612
Use/Application/Characteristics		
Application	• Machine and device construction, transport and conveyor technology, HVAC technology • In dry and damp rooms • As a monitoring, measurement and control cable for industrial applications • For installation in energy chains with constant linear movement	
Characteristics	• Very small cable diameters due to special TPE conductor insulation (HGI) according to UL standard • Reduced friction due to high glide conductor insulation (HGI) for high mechanical loads • Flexibility due to super finely stranded wire construction • Low capacitance, very good electrical properties • Especially developed PVC jacket according to UL class 43 • Filler without wicking • Low adhesion, abrasion-resistant, nick-resistant, tear resistant • Hydrolysis-resistant, microbe-resistant, and rot-resistant • Use in dry or damp environment • Silicone free • RoHS-compliant	
Construction		
Description	SUPERFLEX® N PVC	

02.02.2020 – Subject to technical modification

Part-No. A1481612

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk

Technical data sheet · LÜTZE SUPERFLEX® N PVC

For high requirements

Number of conductors/cross-section	12G1.5
Cross-section AWG	AWG 16
Jacket material	Special PVC
Jacket color	grey RAL 7001
Outer Ø	12.7 mm
Outer Ø	0.5 inch
Weight	203 Lbs/Mft
Cu-Index	113 Lbs/Mft

Element 1

Element construction	AWG 16 / 1,5 mm ²
Conductor	CU-wire bare
Conductor category	Superfinely stranded DIN VDE 0295 IEC 60228, Class 6
Conductor marking	black with white number print green/yellow
Conductor insulation	Special TPE

overall construction

Overall stranding	conductors twisted without mechanical stress layer pitch optimised
Overall wrapping	Fleece taping

Technical data

Rated voltage U _N	600 V UL AWM 105 °C
Test voltage type	3000 V
Temperature range moving	-15 °C ... +90 °C
Temperature range fixed	-40 °C ... +105 °C
Minimum bending radius moving	7.5×D
Minimum bending radius fixed	4×D

Element 1

Element construction	AWG 16 / 1,5 mm ²
Insulation resistance at 20 °C	100 MΩ×km

Certifications/Standards

Certifications	cURus AWM I/II A/B 105°C 600V FT1
UL style	AWM 2586

02.02.2020 – Subject to technical modification

Part-No. A1481612

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet · LÜTZE SUPERFLEX® N PVC

For high requirements

Conformity	CE RoHS REACH
Burning behavior according to	UL VW1, FT1 DIN EN 50265-2-1
Oil resistant according to	UL 4d100C UL Oil Res 80 °C DIN EN 60811-2-1
UV-resistant according to	UL 1581

General

Note CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU

Symbols



02.02.2020 – Subject to technical modification

Part-No. A1481612

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk