AK2GD7550

Cable duct - 50 x 75 mm - without cover - grey



Main	
Product or Component Type	Cable duct
Accessory / separate part categor	Cabling accessories
Range compatibility	PanelSeT S3D PanelSeT CRN Thalassa PLA Thalassa PLS Thalassa PLM
Device Composition	Without cover
Quantity per Set	Set of 8

Complementary

Gray RAL 7030)	
Clip-on support By screws	
PVC (polyvinyl chloride)	
2.0 in (50 mm)	
78.7 in (2000 mm)	
3.0 in (75 mm)	
1.94 lb(US) (0.88 kg)	
250	
	Clip-on support By screws PVC (polyvinyl chloride) 2.0 in (50 mm) 78.7 in (2000 mm) 3.0 in (75 mm) 1.94 lb(US) (0.88 kg)

Environment

Ambient Air Temperature for Operation	23140 °F (-560 °C)
Flame retardance	V-0 UL 94
Fire resistance	1760 °F (960 °C) IEC 60695-2-1/1
Standards	DIN 43659 VDE 0660 VDE 0506

Ordering and shipping details

Category	US1000I22622
Discount Schedule	0001
GTIN	3389110570465
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3.7 in (9.5 cm)	
Package 1 Width	6.7 in (17.0 cm)	
Package 1 Length	78.7 in (200.0 cm)	
Package 1 Weight	24.3 oz (689.9 g)	
Unit Type of Package 2	PAL	
Number of Units in Package 2	200	
Package 2 Height	30.3 in (77.0 cm)	

Package 2 Width	110.2 in (280.0 cm)
Package 2 Length	47.2 in (120.0 cm)
Package 2 Weight	359.4 lb(US) (163.0 kg)
Unit Type of Package 3	CAR
Number of Units in Package 3	8
Package 3 Height	3.7 in (9.5 cm)
Package 3 Width	6.7 in (17.0 cm)
Package 3 Length	78.7 in (200.0 cm)
Package 3 Weight	12.17 lb(US) (5.52 kg)

Offer Sustainability

REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☐ China RoHS Declaration
RoHS exemption information	₫Yes

Contractual warranty

Warranty	18 months