



Main

Range of product	Altivar
Range compatibility	Altivar 312 Solar Lexium 32 Altivar 61 Altivar 71 Lexium 32i Altivar 312 Lexium 52
Product compatibility	ATV312HU55M3 ATV312HU75M3 ATV61HD18N4 ATV61HD22N4 ATV61HD30N4 ATV61HD30Y ATV61HD37Y ATV61HD45Y ATV61HU55M3 ATV61HU75M3 ATV61WD22N4 ATV61WD22N4C ATV61WD30N4 ATV61WD30N4C ATV61WD37N4 ATV61WD37N4C ATV71HD18N4 ATV71HD22N4 ATV71HD22Y ATV71HD30N4 ATV71HD30Y ATV71HD37Y ATV71HU55M3 ATV71HU75M3 ATV71WD18N4 ATV71WD22N4 ATV71WD30N4 LXM32MC10N4 LXM32MD85N4
Continuous power	1000 W
Average power available	1 kW 122 °F (50 °C) 1.154 kW 104 °F (40 °C)
Ohmic value	15 Ohm

Complementary

Electrical connection	M6 bar wire drive Terminal ≤ 2.5 mm ² / AWG 14 temperature control switch
Protection type	Thermal protection via drive or temperature control switch 120 °C
[Ue] rated operational voltage	24 V DC 0.1 A 250 V AC 1 A
Temperature controlled switch contact resistance	60 µOhm
Net Weight	24.25 lb(US) (11 kg)

Environment

Ambient air temperature for operation	32...122 °F (0...50 °C)
Ambient air temperature for storage	-13...158 °F (-25...70 °C)
IP degree of protection	IP20

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Ordering and shipping details

Category	22135-ATV61-71 ACCESSORIES
Discount Schedule	CP4C
GTIN	00785901457466
Nbr. of units in pkg.	1
Package weight(Lbs)	20.89 lb(US) (9.476 kg)
Returnability	No
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	13.15 in (33.4 cm)
Package 1 width	22.44 in (57 cm)
Package 1 Length	16.06 in (40.8 cm)
Unit Type of Package 2	P12
Number of Units in Package 2	6
Package 2 Weight	180.78 lb(US) (82 kg)
Package 2 Height	38.19 in (97 cm)
Package 2 width	47.24 in (120 cm)
Package 2 Length	31.50 in (80 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Braking Resistor

Dimensions

