



### Main

Accessory / separate part categor	Mounting and fixing accessories
Accessory / separate part type	Conformity kit
Degree of protection	UL type 1
Product compatibility	<p>ATV61HC25N4                      ATV61HC25N4D                      ATV61HC25Y                      ATV61HC31N4                      ATV61HC31N4D                      ATV61HC31Y                      ATV61HC40Y                      ATV71HC20N4                      ATV71HC20N4D                      ATV71HC20Y                      ATV71HC25N4                      ATV71HC25N4D                      ATV71HC25Y                      ATV71HC28N4                      ATV71HC28N4D                      ATV71HC31Y                      Variable speed drive ATV630 wall mount 250 kW, normal duty 380...480 V                      Variable speed drive ATV630 wall mount 315 kW, normal duty 380...480 V                      Variable speed drive ATV630 wall mount 220 kW, heavy duty 380...480 V                      Variable speed drive ATV630 wall mount 250 kW, heavy duty 380...480 V                      Variable speed drive ATV930 wall mount 250 kW, normal duty 380...480 V                      Variable speed drive ATV930 wall mount 315 kW, normal duty 380...480 V                      Variable speed drive ATV930 wall mount 250 kW, heavy duty 380...480 V                      Variable speed drive ATV930 wall mount 200 kW, heavy duty 380...480 V</p>
Accessory / separate part destination	Variable speed drive without braking unit
Range Compatibility	<p>Altivar&amp;Nbsp;Process ATV900                      Altivar 71                      Altivar&amp;Nbsp;Process ATV600                      Altivar 61</p>

### Complementary

Kit composition	<p>1 EMC plate                      1 IP54 casing                      Fixing accessories                      1 UL type 1 cover                      1 manual                      1 pre-drilled plate for connecting the tubes</p>
Net Weight	43.0 lb(US) (19.5 kg)

### Environment

Standards	UL Type 1
-----------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Ordering and shipping details

Category	US1CP4C22135
Discount Schedule	CP4C
GTIN	3389119201957
Returnability	Yes
Country of origin	FR

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.4 in (24 cm)
Package 1 Width	19.3 in (49 cm)
Package 1 Length	17.7 in (45 cm)
Package 1 Weight	45.2 lb(US) (20.5 kg)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>

## Contractual warranty

Warranty	18 months
----------	-----------