


Note:
 - Drawings Not To Scale
 - Drawings Subject to Change Without Notice
 - Dimensions are inches next to [Millimeters]

Part No.:

XCKN2110G11



Telemecanique Sensors
 1875 Founders Drive
 Dayton, OH 45420-4017
 Customer Care Center : 1-800-435-2121
 Web : www.tesensors.com

Technical Information:

Terminal Type: Screw Clamp
 Enclosure Rating: NEMA 12, 4X Indoor; IP65
 Approvals: UL # E164353 - CSA # 164581 - CE Marked
 Weight: 0.065 kg (0.140 lb)
 Conforming to Standards: CENELEC EN 50047
 RoHS: Yes
 Operating Temperature Range: -13 to 158 ° F
 Shock Resistance: 50G
 Vibration Resistance: 25G
 Max. Actuation Speed : 0.5 m/s
 Repeat Accuracy: 0.1 mm on the tripping points
 Operating Torque/Force: 133 Inch-Pounds (15Nm)

Specification:

Description: XCKN Limit Switch Metal end plunger
 Body Style/Type Description: IEC OsiSense Limit Switches XCKN Light Duty Monolithic 30mm Plastic Body
 Head Type: Metal end plunger
 Lever Arms:
 Body with Contact Type: 2-pole N.O./N.C. snap action
 Conduit Thread: PG 11
 Ampere Rating Continuous: 10A
 Maximum Voltage Rating: 240VAC/250VDC
 Actuation: Vertical
 Actuator Action: Momentary
 Lever Arm Length:
 Roller Dimension:
 Roller Material:
 Contact Configuration: 1 N.O./1 N.C.
 Contact Operation: Snap Action
 Connection Type: Conduit Entrance (Pg 11)
 Head Material: Plastic
 Positive Opening: Yes
 Cable Length: