




Note:
- Drawings Not To Scale
- Drawings Subject to Change Without Notice
- Dimensions are inches next to [Millimeters]

Part No.:

XCKN2902P20



Telemecanique
Sensors

Telemecanique Sensors
1875 Founders Drive
Dayton, OH 45420-4017
Customer Care Center : 1-800-435-2121
Web : www.tesensors.com

Technical Information:

Terminal Type: Screw Clamp
Enclosure Rating: NEMA 12, 4X Indoor; IP65
Approvals: UL # E164353 - CSA # 164581 - CE Marked
Weight: 0.065 kg (0.140 lb)
Conforming to Standards: CENELEC EN 50047
RoHS: Yes
Operating Temperature Range: -13 to 158 ° F
Shock Resistance: 50G
Vibration Resistance: 25G
Max. Actuation Speed : 0.3 m/s
Repeat Accuracy: 0.1 mm on the tripping points
Operating Torque/Force: 106 Inch-Pounds (12Nm)

Specification:

Description: XCKN Limit Switch Steel top roller plunger
Body Style/Type Description: IEC OsiSense Limit Switches XCKN Light Duty Monolithic 30mm Plastic Body
Head Type: Steel top roller plunger
Lever Arms:
Body with Contact Type: 2-pole N.C./N.C. snap action
Conduit Thread: ISO M20x1
Ampere Rating Continuous: 10A
Maximum Voltage Rating: 240VAC/250VDC
Actuation: Horizontal
Actuator Action: Momentary
Lever Arm Length:
Roller Dimension: 11 x3.5mm
Roller Material: Thermoplastic
Contact Configuration: 1 N.C./1 N.C.
Contact Operation: Snap Action
Connection Type: Conduit Entrance (ISO M20x1.5)
Head Material: Plastic
Positive Opening: Yes
Cable Length: