



**Note:**  
 - Drawings Not To Scale  
 - Drawings Subject to Change Without Notice  
 - Dimensions are inches next to [Millimeters]

Part No.:

**XUB0AKSNL2T**



**Telemecanique**  
 Sensors

Telemecanique Sensors  
 1875 Founders Drive  
 Dayton, OH 45420-4017  
 Customer Care Center : 1-800-435-2121  
 Web : www.tesensors.com

**Technical Information:**

Diffuse with Background Suppression:  
 Diffuse:  
 Polarized Retroreflective:  
 Thru Beam:  
 Retroreflective:  
 Circuit Type:  
 Output Mode:  
 Power: DC  
 Voltage Range: 12-24 VDC  
 Max Load:  
 Max Switching Frequency :  
 Temp Range: -25° to 55° C (-13° to 131° F)  
 NEMA Type: 4X (indoor use only)  
 IP Rating: 67  
 Standards: UL, CE Rohs

**Specification:**

Sensor Type: Thru-Beam Transmitter  
 Description: Photoelectric, Thru-Beam Transmitter, 18 mm Barrel, 12-24 VDC  
 Body Style: Barrel  
 Diameter: 18 mm  
 Housing Material: Plastic - PBT  
 Face Material: PMMA  
 Adjustment:  
 Cable Size: 5.0 m (16.4 ft)  
 Connector Type:  
 Special Features: