




Note:
- Drawings Not To Scale
- Drawings Subject to Change Without Notice
- Dimensions are inches next to [Millimeters]

Part No.:
XUB0BPSNL2



Telemecanique
Sensors

Telemecanique Sensors
1875 Founders Drive
Dayton, OH 45420-4017
Customer Care Center : 1-800-435-2121
Web : www.tesensors.com

Technical Information:

Diffuse with Background Suppression:
Diffuse: 300.0 mm (11.8 in)
Polarized Retroreflective: 2000.0 mm (78.7 in)
Thru Beam: 15000.0 mm (590.6 in)
Retroreflective:
Circuit Type: PNP
Output Mode: Light/Dark Operate
Power: DC
Voltage Range: 12-24 VDC
Max Load: 100 mA
Max Switching Frequency : 250 Hz
Temp Range: -25° to 55° C (-13° to 131° F)
NEMA Type: 4X (indoor use only)
IP Rating: 67
Standards: UL, CE Rohs

Specification:

Sensor Type: Multi-Mode
Description: Photoelectric, Multi-Mode, 18 mm Barrel, 12-24 VDC
Body Style: Barrel
Diameter: 18 mm
Housing Material: Metal - NPB
Face Material: PMMA
Adjustment: Pushbutton teach
Cable Size:
Connector Type:
Special Features: