



Note:
 - Drawings Not To Scale
 - Drawings Subject to Change Without Notice
 - Dimensions are inches next to [Millimeters]

Part No.:

XUK0ARCTL2T



Telemecanique
 Sensors

Telemecanique Sensors
 1875 Founders Drive
 Dayton, OH 45420-4017
 Customer Care Center : 1-800-435-2121
 Web : www.tesensors.com

Technical Information:

Diffuse with Background Suppression: 300.0 mm (11.7 in)
 Diffuse:
 Polarized Retroreflective:
 Thru Beam:
 Retroreflective:
 Circuit Type:
 Output Mode:
 Power: AC/DC
 Voltage Range: 20-240
 Max Load:
 Max Switching Frequency :
 Temp Range: -25° to 55° C (-13° to 131° F)
 NEMA Type: 4X (indoor use only)
 IP Rating: 65
 Standards: UL, CE Rohs

Specification:

Sensor Type: Thru-Beam Transmitter
 Description: Photoelectric, Thru-Beam Transmitter, Small Rectangle, 20-240
 Body Style: Small Rectangle
 Diameter:
 Housing Material: Plastic - PBT
 Face Material: PMMA
 Adjustment:
 Cable Size: 2.0 m (6.6 ft)
 Connector Type:
 Special Features: Hinged cover