



Note:

- Drawings Not To Scale
- Drawings Subject to Change Without Notice
- Dimensions are inches next to [Millimeters]

Part No.:

XUK9ARCNL2



Telemecanique
Sensors

Telemecanique Sensors
1875 Founders Drive
Dayton, OH 45420-4017
Customer Care Center : 1-800-435-2121
Web : www.tesensors.com

Technical Information:

Diffuse with Background Suppression:
 Diffuse:
 Polarized Retroreflective: 5000.0 mm (196.9 in)
 Thru Beam:
 Retroreflective:
 Circuit Type: AC/DC Relay
 Output Mode:
 Power: AC/DC
 Voltage Range: 20-240
 Max Load: 3000 mA
 Max Switching Frequency : 20 Hz
 Temp Range: -25° to 55° C (-13° to 131° F)
 NEMA Type: 4X (indoor use only)
 IP Rating: 65
 Standards: UL, CE Rohs

Specification:

Sensor Type: Transparent Material Detection - Polarized Retroreflective
 Description: Photoelectric, Transparent Material Detection - Polarized Retroreflective, Small Rectangle, 20-240
 Body Style: Small Rectangle
 Diameter:
 Housing Material: Plastic - PBT
 Face Material: PMMA
 Adjustment: No
 Cable Size: 2.0 m (6.6 ft)
 Connector Type:
 Special Features: Hinged cover