# ZC2JE62

Limit switch head, Limit switches XC Standard, ZC2J, steel roller plunger





# Main

Range of Product	OsiSense XC
Series name	Special format
Product or Component Type	Limit switch head
Device short name	ZC2J
Head type	Plunger head
Product Compatibility	XC2J
Associated body	ZC2JD1 ZC2JC1 ZC2JC28 ZC2JD2 ZC2JC2 ZC2JC18
Movement of operating head	Linear
Type of operator	Roller plunger spring return metal
Type of approach	Lateral approach, 2 directions

#### Complementary

Switch actuation	By 30° cam
Positive opening	Without
Net Weight	0.44 lb(US) (0.2 kg)
Head material	Metal

#### Environment

Ambient Air Temperature for Operation	-13158 °F (-2570 °C)
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)
Environmental characteristic	Standard environment

### Ordering and shipping details

Category	22449-LIMIT SWITCHES,ACCESSORIES
Discount Schedule	Т
GTIN	3389110324044
Returnability	No
Country of origin	FR

## Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	1.97 in (5.0 cm)	
Package 1 Width	3.70 in (9.4 cm)	
Package 1 Length	1.89 in (4.8 cm)	
Package 1 Weight	7.55 oz (214.0 g)	
Unit Type of Package 2	S01	
Number of Units in Package 2	14	
Package 2 Height	5.91 in (15.0 cm)	
Package 2 Width	5.91 in (15.0 cm)	

Package 2 Length	15.75 in (40.0 cm)	
Package 2 Weight	7.04 lb(US) (3.193 kg)	
Offer Sustainability		
Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS  Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	
Contractual warranty		
Warranty	18 months	