



Main

Range of Product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or Component Type	Limit switch head
Device short name	ZCKE
Head type	Multi-directional head
Product Compatibility	XCKJ
Associated body	ZCKJ2H7 ZCKJ1 ZCKJD31H7 ZCKJ8H29 ZCKJD35 ZCKJ21H29 ZCKJD39H29 ZCKJ7H29 ZCKJD37H7 ZCKJD37H29 ZCKJ11H29 ZCKJ9 ZCKJ1H7 ZCKJ6 ZCKJ1H29 ZCKJ5 ZCKJ8 ZCKJ7 ZCKJ2 ZCKJ21H7 ZCKJD37 ZCKJD35H29 ZCKJ9H29 ZCKJ5H7 ZCKJ21 ZCKJ6H7 ZCKJ7H7 ZCKJ2H29 ZCKJD31 ZCKJD35H7 ZCKJ8H7 ZCKJD39 ZCKJ11H7 ZCKJ11 ZCKJD31H29 ZCKJ9H7 ZCKJD39H7 ZCKJ5H29 ZCKJ6H29
Movement of operating head	Multi-directional
Type of operator	Cat's whisker spring return
Type of approach	Multi-directional approach

Complementary

Switch actuation	By any moving part
Positive opening	Without
Net Weight	0.25 lb(US) (0.115 kg)
Head material	Metal

Environment

Ambient Air Temperature for Operation	-40...158 °F (-40...70 °C)
Ambient Air Temperature for Storage	-40...158 °F (-40...70 °C)
Environmental characteristic	Low temperature

Ordering and shipping details

Category	22411-LIMIT SWITCHES,IEC,XCKJ
Discount Schedule	T
GTIN	3389118130616
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.30 in (16.0 cm)
Package 1 Width	1.42 in (3.6 cm)
Package 1 Length	1.42 in (3.6 cm)
Package 1 Weight	4.06 oz (115.0 g)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------