

ZCKE645

Limit switch head, Limit switches XC Standard, ZCKE, side steel roller plunger horizontal, +120 °C



ZCK E64

Main

Range of Product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or Component Type	Limit switch head
Device short name	ZCKE
Head type	Plunger head
Product Compatibility	XCKJ
Associated body	ZCKJD37H7 ZCKJD31H29 ZCKJ8 ZCKJD31H7 ZCKJ21H7 ZCKJ6H29 ZCKJ6H7 ZCKJ11H7 ZCKJD39H29 ZCKJ7 ZCKJ9H7 ZCKJD39 ZCKJD31 ZCKJ2 ZCKJ1H7 ZCKJ1 ZCKJD37H29 ZCKJ21 ZCKJ8H7 ZCKJD39H7 ZCKJ5H7 ZCKJ21H29 ZCKJD35H7 ZCKJD35H29 ZCKJ6 ZCKJ7H29 ZCKJ11H29 ZCKJ9 ZCKJ8H29 ZCKJ5 ZCKJ1H29 ZCKJ5H29 ZCKJ11 ZCKJ7H7 ZCKJ2H7 ZCKJ2H29 ZCKJD37 ZCKJD35 ZCKJ9H29
Movement of operating head	Linear
Type of operator	Side roller plunger spring return metal with horizontal roller)
Type of approach	Lateral approach, 2 directions

Complementary

Switch actuation	By 30° cam
Positive opening	With
Net Weight	0.45 lb(US) (0.205 kg)
Head material	Metal

Environment

Ambient Air Temperature for Operation	50...248 °F (10...120 °C)
Ambient Air Temperature for Storage	50...248 °F (10...120 °C)
Environmental characteristic	High temperature

Ordering and shipping details

Category	22411-LIMIT SWITCHES,IEC,XCKJ
Discount Schedule	T
GTIN	3389110599466
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.57 in (4.0 cm)
Package 1 Width	1.77 in (4.5 cm)
Package 1 Length	3.35 in (8.5 cm)
Package 1 Weight	6.56 oz (186.0 g)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------