

 Catalog Number:
 GRFR-187-WH-C

 Product ID:
 7TAG009750R0015

 UPC Number:
 72849414298

 EAN Number:
 05415022359459

Status: Active

Extruded Grommeting, Flame Retardant White Polyethylene, Height of 6.86mm (0.27 Inches), Width of 6.98mm (0.275 Inches), Thickness 1.32mm (0.05 Inches), Maximum Panel Thickness of 4.75mm (0.187 Inches), 30.48m (100 Foot) Reel

- Used to line panel edges and knockouts where the chafing of wires is a concern.
- Available in 8 stock sizes in 100-ft. lengths for panels from .040 .250 inches thick and in a variety of stocked materials to cover a wide range of applications.

UNSPSC Specifications	
UNSPSC	39131603 Grommet edging
IGCC	5393 Grommet edging
Brand Name	Catamount
Туре	Grommeting
Special Features	Used to line panel edges and knockouts where the
	chafing of wires is a concern.
Color	White
Panel Thickness	0.187
Material	Flame Retardant Polyethylene
Packaging	
Inner Quantity	1
Inner Dimensions (inches)	3x3x3
Outer Quantity	10
Outer Dimensions (inches)	18x12x13
Weight Uom	2.2 lbs. Each

Documents / Support Tools

Technical Data Sheet CA Available on Website

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Actual

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com