

**ZQV 1.5N/R6.4/19 GE****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image****General ordering data**

|                     |                             |
|---------------------|-----------------------------|
|                     |                             |
| Version             | TERMSERIES, Cross-connector |
| Order No.           | <a href="#">1193690000</a>  |
| Type                | ZQV 1.5N/R6.4/19 GE         |
| GTIN (EAN)          | 4032248976645               |
| Qty.                | 10 pc(s).                   |
| Delivery status     | Discontinued                |
| Available until     | 2021-06-30                  |
| Alternative product | <a href="#">2556370000</a>  |

**ZQV 1.5N/R6.4/19 GE****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Depth      | 4.9 mm  | Depth (inches)  | 0.193 inch |
| Height     | 13.1 mm | Height (inches) | 0.516 inch |
| Width      | 119 mm  | Width (inches)  | 4.685 inch |
| Net weight | 4.647 g |                 |            |

**Temperatures**

|                     |                |                       |                |
|---------------------|----------------|-----------------------|----------------|
| Storage temperature | -40 °C...85 °C | Operating temperature | -40 °C...60 °C |
|---------------------|----------------|-----------------------|----------------|

**Rated data UL**

|                    |      |
|--------------------|------|
| Rated current (UL) | 10 A |
|--------------------|------|

**General data**

|         |                      |        |        |
|---------|----------------------|--------|--------|
| Version | can be cut to length | Colour | yellow |
|---------|----------------------|--------|--------|

**Insulation coordination**

|               |       |
|---------------|-------|
| Rated voltage | 250 V |
|---------------|-------|

**Connection data**

|                 |        |
|-----------------|--------|
| Pitch in mm (P) | 6.4 mm |
|-----------------|--------|

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002586    | ETIM 7.0    | EC002586    |
| ETIM 8.0    | EC002586    | ETIM 9.0    | EC002586    |
| ETIM 10.0   | EC002586    | ECLASS 9.1  | 27-37-16-92 |
| ECLASS 10.0 | 27-37-16-92 | ECLASS 11.0 | 27-37-16-92 |
| ECLASS 12.0 | 27-37-16-92 | ECLASS 13.0 | 27-37-16-92 |
| ECLASS 14.0 | 27-37-16-92 | ECLASS 15.0 | 27-37-16-92 |

**Environmental Product Compliance**

|                        |                             |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC             | No SVHC above 0.1 wt%       |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                    |                                                               |
|--------------------|---------------------------------------------------------------|
| Engineering Data   | <a href="#">CAD data – STEP</a>                               |
| User Documentation | <a href="#">Beipackzettel / Package Insert - multilingual</a> |
| Catalogues         | <a href="#">Catalogues in PDF-format</a>                      |
| Brochures          |                                                               |

## ZQV 1.5N/R6.4/19 GE

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

# Drawings

## Dimensional drawing

